

Flexible

The FD 380 is capable of processing paper up to 17”(432mm) in length and up to 12.25”(311mm) in width giving it the flexibility to process a variety of paper lengths and widths. The ability to customize jobs allows operators to fold in virtually any configuration that only requires two folds. Cross folding adds to the 380’s flexibility allowing for additional folds in a second pass.

The unique semi-automatic **Dedicated Multi-Sheet Feeder** is designed with an independent skew adjuster, side guide adjuster and paper sensor allowing operators to accurately fold stapled and unstapled sets of precollated documents with up to three 20#(75gsm) sheets.

Accurate

Self centering side guides and a skew adjuster ensure that paper is loaded and feeds squarely into the folder. Fine tuning knobs on the fold plates allow operators to precisely set the fold positions.

Operator Friendly

Pre-programmed folds, automatic fold adjustments, and a centrally located control panel make for easy set-up and operation. The **Telescoping Outfeed Stacker**, with an unprecedented stacking capability of up to 500 folded documents, cuts down on unloading time and ensures that the forms remain in a neat and sequential order.

The unique **AutoBatch™** or “automatic batch” allows operators to batch count with automated features. In the AutoBatch mode, operators can program the number of sheets to be processed in a set, the number of sets needed and the delay between each set.

Pre-Programmed Fold Types



Letter



Zig-Zag



Single



Gate



Fold Out



Double Parallel

Specifications:

Hopper Capacity:	Up to 500 Sheets 20# (75gsm)
Variable Speed:	Up to 12,500 sheets per hour - based on 11”(279mm) “Z” fold
Paper Size:	Min: 3.5” W x 5” L (88.9 W x 127 L mm) Max: 12.25” W x 17” L (311 W x 432 L mm)
Power:	FD Model: 120 Volts AC 50/60 HZ FE Model: 220 Volts AC 50/60 HZ
Dimensions:	Closed: 33” L x 20” W x 19” H (84 L x 51 W x 48 H cm) Fully Extended: 60” L x 20” W x 19” H (152 L x 51 W x 48 H cm)
Weight:	77 lbs (35 kg)
Certifications:	UL and CUL approved CE applied for



User friendly control panel



Multi-Sheet Feeder



Closed Stacker



A **400 Series Jogger** is a recommended option that reduces static electricity from forms and aligns them for proper feeding