

# FORMAX<sup>®</sup>

Div. of BESCORP, Inc.

## Model FD 594

MULTI-STATION DECOLLATOR

### Standard Features:

- **FD 592** - two stations
- **Tractor feed**
- **Margin slitters**
- **Safety jog switches**

### Options:

- **FD 593** - three stations
- **FD 594** - four stations
- **FD 595** - five stations
- **FD 596** - six stations
- One-part add-on center slitter
- Paper control rod for carbonless forms



**Continuous Form Decollators** Three models are available to process both carbon interleaved and carbonless multi-part forms. The two-part decollators are easy to use and are available in both tabletop and floor models. Our multi-station decollator is capable of processing up to six part forms fast, clean and efficiently. The multi-station decollator offers the flexibility to add stations as applications grow.

Distributed by **RELYCO**  
100 Main St Ste 222, Dover NH 03820  
www.relyco.com info@relyco.com

**1-800-777-7359**

SPECIFICATIONS	Speed:	Variable, 0 - 475 feet/minute
	Form size:	2 3/4" - 19" width (slitting) 2 3/4" - 17 7/8" width (non- slitting) Up to 14"
	Power:	115 Volts AC 50/60 Hz.
	Weight:	FD 592 - 235 lbs. • 1-Part Add-On - 50 lbs.
	Dimensions:	44"L x 38"W x 46"H (FD 592)
	Certifications:	UL

## CONTINUOUS FORM DECOLLATORS

### TWO-PART DECOLLATOR

SPECIFICATIONS	Speed:	Variable, 0 - 450 feet/minute
	Form size:	Up to 21" width
	Power:	115 Volts AC 50/60 Hz.
	Weight:	89 lbs.
	Dimension:	49"L x 26"W x 14"H
	Certifications:	UL



### TWO-PART TABLETOP DECOLLATOR

SPECIFICATIONS	Speed:	Variable, 0 - 400 feet/minute
	Form size:	Up to 16" width
	Rewind Spindle:	Up to 650 feet cap.
	Power:	115 Volts AC 50/60 Hz.
	Weight:	89 lbs.
	Dimension:	49"L x 26"W x 14"H
Certifications:	UL	

