



The ST9550sd offers the extensive security features found in Source Technologies' MICR printers, but for use in secure printing applications using Lexmark standard toner.

Speed (pages per minute)	50 ppm
Time to First Page	< 8.5 seconds
Network Options Available	Yes
Processor	514 MHz
Memory (standard/maximum)	128 MB RAM/640 MB RAM
Compatibility	Postscript 3, PCL6, PPDS, PCL5e*
Connectivity Options	USB, Parallel, e-net
Maximum Resolution	1,200 x 1,200 dpi
Paper Capacity (sheets)	
○—  Standard (in/out)	600/500
○—  Maximum (in/out)	4,100/3,000
Paper Sources	
○—  Standard (in/out)	2/1
○—  Maximum (in/out)	7/11
Duty Cycle	Up to 250,000 pgs./mo.
Cartridge Options	Starter cartridge: 6,000 Replacement cartridge:21,000/32,000
Dimensions (W" x D" x H")	17.2 x 20.6 x 16
Weight (lbs.)	51
Warranty	1 year return from date of sale
Security Features	Print Protection Set Copies to one (1) Auto Jam Recovery Disable Password Protection MicroPrint & Secure Numeric Font Audit Trail Reporting Datastream Decryption DES & AES Datastream Tray Protection Bi-Directional Communication Tray Locking Option

\* Secure Document features require use of PCL5e

# ST9550sd

