

Standard Features

- **Automatic alignment:** Assures accurate imprint locations
- **Dual key/lock controls:** Provides maximum access control
- **Counters:** Resettable and non-resettable counter for audit purposes
- **Imprint designs:** Signatures, endorsements, seals and logos
- **Imprint location:** Anywhere within the specified paper dimensions
- **Bottom feed:** Assures proper sequencing of documents and continuous operation

Options:

- **Tri-color and ultraviolet ink roll**
- **Stand**
- **400 Series Jogger**



FD 150

Two signers are available to process both cut-sheet and continuous documents. The FD 150 allows the versatility of imprinting signatures, endorsements, seals and logos onto cut-sheet documents. The FD 130 combines all of the traditional continuous signing capabilities with ten programmable imprint settings. All of our signers include dual key/lock controls and both resettable and non-resettable counters for maximum audit capability.

Specifications: FD150

Hopper Capacity:	Up to 200 sheets
Speed:	Up to 300 documents/minute
Paper Size:	2.75" - 14" width 3" - 14" length
Imprint Size:	Standard size - .875" x 3" Optional size - 1.875" x 3"
Power:	115 volts AC 50/60 Hz
Weight:	40 lbs.
Dimensions:	12" L x 19.5" W x 9.5" H
Safety Certifications:	UL



121 Broadway • Dover NH 03820
T (800) 777-7359 • (603) 742-0999 F (603) 742-9993
E info@relyco.com www.relyco.com

FD 130 CONTINUOUS FORM SIGNER

Standard Features:

- **Programmable memory:** Document sizes and imprint locations for up to ten jobs
- **Dual key/lock controls:** Provides maximum access control
- **Counters:** Resettable and non-resettable counters for audit purposes
- **Imprint designs:** Signatures, seals and logos
- **Imprint location:** Anywhere within the specified paper dimensions

Options:

- **Tri-color and ultraviolet ink roll**
- **Stand**

Specifications: FD 130

Speed:	Up to 325 documents/minute
Paper Size:	5" - 18" maximum width 2.75" - 17" length
Imprint Size:	Standard size - .875" x 3"
Power:	115 volts AC 50/60 Hz
Weight:	39 lbs.
Dimensions:	9" L x 25.25" W x 14.75" H
Safety Certifications:	UL



FD 130