

FORMAX[®]

590 Series

MULTI-STATION DECOLLATORS

Standard Features

- **FD 592:** Two stations
- **Tractor Feed:** Aligns and prevents misfeeding
- **Margin Slitters:** Trims margins from one or both sides of the form
- **Safety Jog Switches:** For convenient loading and form control
- **Variable Speed:** 0 - 475 feet per minute
- **Safety Covers:** Clear plexi covers with safety interlock switches

Options:

- **FD 593:** Three stations
- **FD 594:** Four stations
- **FD 595:** Five stations
- **FD 596:** Six stations
- **One-part add-on**
- **Center slit**
- **Paper control rod for carbonless forms**



FD 594

Continuous Form Decollators

The Formax multi-station decollator is capable of processing up to six-part forms, both carbon interleaved and carbonless multi-part forms. The multi-station decollator offers the flexibility to add stations as applications grow, and separates forms cleanly, quickly and efficiently.

Specifications:

Speed:	Variable, 0 - 475 feet per minute
Form Size:	2 3/4" to 19" width (slitting) 2 3/4" to 17 7/8" width (non-slitting) Up to 14" length
Power:	115 volts AC 50/60 Hz
Weight:	FD 592: 235 lbs. 1-part add-on: 50 lbs.
Dimensions:	54" L x 30" W x 39" H (FD 592) Additional 13.5" L per 1-part add-on
Safety Certifications:	UL

RELYCO
BUSINESS PRINTING SOLUTIONS[®]

121 Broadway • Dover NH 03820
T (800) 777-7359 • (603) 742-0999 F (603) 742-9993
E info@relyco.com www.relyco.com